

**BOTTOM THREAD**

**SERIES 201/G**

**PROBE P201/G**

**Recommended minimum centres: 4.0mm**

**MECHANICAL**  
Full travel: 5.0mm  
Recommended working travel: 4.0mm  
Switch travel: 1.7mm

**SPRING FORCE**  
Preload: 0.25N 0.4N 0.6N 1.4N 2.0N  
@ Working travel: 1.25N 2.3N 3.5N 7.0N 10.0N  
Switch travel: 0.45N 1.0N 1.6N 3.6N 5.2N

**ORDER PART NO.**  
ELECTRICAL  
Max current: 1 amp  
Terminal resistance: <25m ohms  
Insulation voltage: 1KV  
Recommended hole size: 3.5mm

STANDARD FORM      LONG FORM

**TIP STYLES**

**P201/G-A**      **P201/G-AL/AL1**      **P201/G-C/C4/C6**

STEEL / BeCu      LONG FORM STEEL / BeCu      STEEL / BeCu

**P201/G-C1**      **P201/G-C2/C7/C8/C9**      **P201/G-CL/CL6/CL8**      **P201/G-CL1**      **P201/G-CL2**      **P201/G-FO/F3**      **P201/G-F/F1**

STEEL / BeCu      BeCu      STEEL / BeCu      STEEL / BeCu      STEEL / BeCu      STEEL / BeCu      STEEL / BeCu

**P201/G-F1/F2/F4-POM**      **P201/G-FL**      **P201/G-FL3**      **P201/G-K**      **P201G-FS1/F2/F4**      **P201/G-F5/F6/F7/F8**      **P201/G-FS1/F5/F6/F7/F8-POM**

NYLON      BeCu      BeCu      STEEL      BeCu      BeCu      NYLON

**RECEPTACLES**

**R201/G-K**      **R201/G-5K**      **R201/G-KB**

21, 38, 12, 5.0, 0.2, 31.7, 5.0, Ø3.0, Ø3.02, Ø3.06, Ø3.2, Ø2.95, Ø2.5

Solder free replacement and height adjustment

**P201/G-FL1/FL5**      **P201/G-FL6/FL8**      **P201/G-FL1/FL3/FL5-POM**

BeCu      BeCu      NYLON

**PROBE ORDER CODE**  
**P201/G - A - 1**  
Series Tipstyle Spring Force

Note: Tip Material shown Black - Standard Stock Item Blue - Optional On Request Purple = Minimum order quantity