

A FULL PRICE LIST WITH PRICE BREAKS IS AVAILABLE BY E-MAIL ON REQUEST FROM: peak.test@thepeakgroup.com

**PLEASE PHONE
0191 387 1923 FOR
TECHNICAL ASSISTANCE**

SELECTING THE CORRECT TIP STYLE

STYLE A/P




CONCAVE/CUP
90° concave tip for probing wire-wrap terminals, connector pins, component leads and feed-through terminals.

STYLE B



30° POINT/SPEAR
For penetration of oxides, fluxes and some conformal coatings (use higher spring rating).

STYLE BST STEEL




10° POINT
This very sharp probe will penetrate any concentration of fluxes, oxides and conformal coatings. It can also be used in special fixtures for testing hybrids and micro-miniature circuitry.

STYLE BT80 STEEL



STEEL 4-SIDED DAGGER
For S.M.D. via hole and pads.

STYLE C



SERRATED
Sharp points provide good electrical contact over larger target areas, e.g. bent component leads, without deflection.

STYLE D



DOME HEAD
For screws, terminal blocks and edge connector fingers.

STYLE E




90° POINT/CONE
Application similar to Style B, and for contacting clean base metal, through-plated holes and connector sockets.

STYLE F




FLAT HEAD
For damage-free probing of rounded surfaces.

STYLE FN



FLEXIBLE NEEDLE
Similar application as for BST.

STYLE G




4-POINT CROWN
For component leads, soldering points and test pads where there is no excessive dirt.

STYLE H




PYRAMID 3-SIDED CHISEL
For cutting through contaminants on through-plated holes.

STYLE I/DI



ROUND HEAD
For connector probing.

STYLE K



STAR/FLUTED
Through-plated holes, lands, pads. Self-cleaning sharp point.

STYLE L



4-POINT HEADLESS CROWN
For soldered joints and straight device leads.

STYLE M1



7-POINT TULIP CROWN WITH CENTRE POINT
Most popular tip for general use, self-cleaning.

STYLE 3N



VERY SHARP 3 NEEDLE
For lands, pads, component leads. For good penetration of unclean surfaces.

STYLE Q



3 or 4 POINTS REDUCED CROWN SELF-CLEANING
For use on dirty boards for contacting soldered pads, joints and component leads.

STYLE Q5



3-POINT CROWN SELF-CLEANING
Application as for L, but with a better distribution of force over 3 points.

STYLE S




SELF-CLEANING UNIVERSAL TAPERED 4-POINT CROWN

STYLE SU



3 or 4 POINTS SELF-CLEANING REDUCED CROWN - 0.5mm DIA
For use on S.M.D. boards.

STYLE T



TRI-NEEDLE
Lands, unclean pads, component leads. Self-cleaning.

STYLE W



120° INVERTED HEXAGONAL CONE
For w/w posts or bent pins.

STYLE Y



SPADE/BLADE
For application with test probes in connector systems.

STYLE Z



8-POINT CROWN
Leads, connector pins. 8 points ensure good capture of misaligned component leads. Self-cleaning.